



KEBANA DECOR

Code 3736
Sheet 632
Edition 01.10.10
Page 1 di 2

Colorificio Adriatico srl
Industria Italiana Colori _Italia_Lucrezia 61030 PU Via Pilone 82 _Tel 0721.897.100 Fax 0721.899.596 www.colorificioadriatico.it

GENERAL CHARACTERISTICS

Name

Kebana Decor

Description

Creative, decorative washable paint, breathable, anti-mould, free from volatile organic compounds (VOC.Zero.Zero) for polychromatic finishes, with an antique effect, to enhance prestigious interiors and with respect to the environment and humans.

Classification UNI 8681

Paint for finishing coat dispersed in water, single component, physical drying, matt, acrylic.
(B4.C.0.A.2.FA)

Use

Internal

Type of substrate

Any type of substrate (wall, wood, metal, plasterboard, etc.) previously treated with suitable priming procedures.

TECHNICAL SPECIFICATIONS

Physical state: liquid

Appearance: matt

Type of binder: acrylic

Density (specific weight): 1010 ± 50 g/L

Viscosity: thixotropic

Colour range: KEBANA DÉCOR colour card

APPLICATION CHARACTERISTICS

Environmental conditions

Ambient temperature: min. + 5°C max. +40°C. Ambient relative humidity: max. 80%.

Preparation of the substrate

The substrates must be properly prepared with suitable procedures, depending on the type of substrate.

Application technique: brush, flexible spatula.

Diluent: water

Dilution: 5% max.

Application method: Apply two coats of UNIFOND GROB primer. Choose the UNITONER colour and add it to KEBANA DÉCOR, in the quantity indicated on the colour card and correctly mix together. Once mixed, the product is ready to use; if necessary it can be diluted with water 5% max. Apply with a suitable spatula paintbrush, using a criss-cross technique, taking care not to cover surfaces larger than 2 m² at one time. After approx. 5-10 minutes, delicately smooth the product with the flexible spatula to create the desired decoration. Continue to apply the product with the same technique, until completion of the work.

Drying at 25°C and 65% relative humidity: 2-3 hours on the surface, 48-72 hours curing.

Number of layers: 1

Coverage: 8-10 m²/L per coat. Advised consumption per m²/: 125-100 ml. per coat.

Coverage per container for one coat: 2.5 L_20-25 m² approx., 12.5 L_100-125 m² approx.

Coverage can vary depending on the absorbency of the substrate.

Over-coating with other products: With all water-based products.

STORAGE

Containers: 2.5 – 12.5 L in plastic

Storage conditions: Min. and max. temp: +5°C +30°C.



KEBANA DECOR

Code 3736
Sheet 632
Edition 01.10.10
Page 2 di 2

Colorificio Adriatico srl
Industria Italiana Colori _Italia_Lucrezia 61030 PU Via Pilone 82 _Tel 0721.897.100 Fax 0721.899.596 www.colorificioadriatico.it

SAFETY AND ENVIRONMENTAL SAFETY

Classification in relation to hazards: Does not require hazard labelling under the regulations relative to the directive 67/548/EEC and 1999/45/EC and subsequent amendments and adjustments. For further information, it is possible, upon request, to consult the relevant safety data sheet.

Types of waste: If the plastic packaging, after the use of the product contained in it, contains a quantity of dry residue of less than 1%, it could be sent to the recovery or recycling as waste bearing the code CER 150102. In any case, the local regulations need be taken into account.

ITEM SPECIFICATIONS

Application of two coats of UNIFOND GROB. Application of KEBANA DECOR with successive smoothing of the surface, washable decorative paint, breathable, anti-mould, free from volatile organic compounds (VOC.Zero.Zero), for polychromatic finishes, with an antique effect, with an average coverage of 8-10 m²/L.

As application conditions and the possibility of use can be influenced by elements outside of the possibility of control by Colorificio Adriatico, the company does not assume any responsibility on the outcome of the results.