



KEBANA FONDERIA

Code 3511
Sheet 804
Edition 29.05.18
Page 1 di 2

Colorificio Adriatico srl
Industria Italiana Colori _Italia_Lucrezia 61030 PU Via Pilone 82 _Tel 0721.897.100 Fax 0721.899.596 www.colorificioadriatico.it

GENERAL CHARACTERISTICS

Name

Kebana Fonderia

Description

Mineral coating for internal and external use, based on lime, synthetic binder and high quality marble powders. Once applied to the wall, providing a soft and velvety effect like the washed cement.

Use

Internal/external

Type of substrate

Concrete plasters, painted plasters, precast concrete, Lime-based Plasters, Plasterboards.

TECHNICAL SPECIFICATIONS

Physical state: pasty

Appearance: semigloss

Type of binder: lime and synthetic binder

Density (specific weight): 1500 + 50 g/L

Solid contents in weight: 67%

Viscosity: pasty

Colour range: white or coloured

APPLICATION CHARACTERISTICS

Environmental conditions

Ambient temperature: min. + 5°C max. +40°C. Ambient relative humidity: max. 80%.

Preparation of the substrate

Clean the surface from any dust and dirt. Apply one coat of Kebana Decoprimer and wait at least 8 hours.

Application technique: Spatula, Stainless steel trowel

Diluent: Water

Dilution: Ready to use

Application method: Use a stainless steel trowel to apply one or more coats of the product (wait at least 2 hours between each coat); smooth the surface to obtain a flat finish. Spray some water on the second coat through vaporizer and then smooth the surface with trowel steel until you get the final effect. If you do not want to see black streaks smooth with a plastic trowel. You can also polish the final coat with sandpaper in order to obtain the final effect.

Drying at 25°C and 65% relative humidity: 6-8 hours in depth.

Number of layers: 1 or more

Coverage: 2 m²/kg per coat.

Coverage can vary depending on the absorbency of the substrate.

Over-coating with other products: With this product or all water-based products.

STORAGE

Containers: 5 -20 KG in plastic

Storage conditions: Min. and max. temp: +5°C +30°C.



KEBANA FONDERIA

Code 3511
Sheet 804
Edition 29.05.18
Page 2 di 2

Colorificio Adriatico srl
Industria Italiana Colori _Italia_Lucrezia 61030 PU Via Pilone 82 _Tel 0721.897.100 Fax 0721.899.596 www.colorificioadriatico.it

SAFETY AND ENVIRONMENTAL SAFETY

Classification in relation to hazards: Requires hazard labelling under the regulations relative to the directive 67/548/EEC and 1999/45/EC and subsequent amendments and adjustments. For further information, it is possible, upon request, to consult the relative safety data sheet.

Types of waste: If the plastic packaging, after the use of the product contained in it, contains a quantity of dry residue of less than 1%, it could be sent to the recovery or recycling as waste bearing the code CER 150102. In any case, the local regulations need be taken into account.

ITEM SPECIFICATIONS

Application of one or two layers of KEBANA FONDERIA, decorative plaster for internal and external use, based on lime, synthetic binder and quality coloured powders, to obtain a soft and velvety like the washed cement, with an average coverage of 1.6-2 m²/kg per coat.

As application conditions and the possibility of use can be influenced by elements outside of the possibility of control by Colorificio Adriatico, the company does not assume any responsibility on the outcome of the results
